TRACTAGRI XEP 15W-40



Mineral lubricant for diesel engines

SPECIFICATIONS AND APPROVALS

Mahindra and Mahindra

APPLICATIONS

- ❖ Total Tractagri XEP 15W 40 is recommended for all naturally -aspirated diesel engines of agricultural applications
- This lubricant is well suited for all industrial vehicles operating under severe service conditions (high temperature, frequent stops...).
- ❖ Total Tractagri XEP15W 40 is specifically recommended for diesel engines from heavy duty to extremely heavy duty.

PERFORMANCES AND CUSTOMER BENEFITS

- ❖ Total Tractagri XEP 15W-40 has excellent oxidation resistance, guaranteeing efficient engine protection under normal and severe conditions.
- Detergent, dispersant and anti-wear properties keep the engine clean and enable effective control of soot, sludge and piston deposits.
- ❖ Total Tractagri XEP 15W-40 exhibits superior protection against heat and wear ensuring long engine life.

PHYSICAL AND CHEMICAL CHARACTERISTICS

Parameter	Unit	Method	Typical Value
Density	kg/m³	ASTM D 1298	866
Kniematic Viscosity at 40°C	cSt	ASTM D 445	111.5
Kinematic Viscosity at 100°C	cSt	ASTM D 445	14.3
Viscosity Index		ASTM D 2270	131

TRACTAGRI XEP 15W-40



RECOMMENDATIONS

- ❖ Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.
- ❖ The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.
- All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.