TRACTAGRI ULTRA T3R 15W-40



Mineral lubricant for diesel engines

SPECIFICATIONS AND APPROVALS

API CI - 4

APPLICATIONS

- Tractagri Ultra T3R 15W 40 is recommended for all naturally-aspirated diesel engines of agricultural applications requiring API CI -4 performance.
- This lubricant is well suited for all industrial vehicles operating under severe service conditions (high temperature, frequent stops...).
- Tractagri Ultra T3R 15W 40 is specifically recommended for diesel engines from heavy duty to extremely heavy duty.

PERFORMANCES AND CUSTOMER BENEFITS

- Tractagri Ultra T3R 15W -40 has excellent oxidation resistance, guaranteeing efficient engine protection under normal and severe conditions.
- Detergent, dispersant and anti-wear properties keep the engine clean and enable effective control of soot, sludge and piston deposits.
- Tractagri Ultra T3R 15W-40 exhibits superior protection against heat and wear ensuring long engine life.

PHYSICAL AND CHEMICAL CHARACTERISTICS

Parameter	Unit	Method	Typical Value
Density	kg/m ³	ASTM D 1298	870
Kniematic Viscosity at 40°C	cSt	ASTM D 445	99.2
Kinematic Viscosity at 100°C	cSt	ASTM D 445	14.1
Viscosity Index		ASTM D 2270	143

TRACTAGRI ULTRA T3R 15W-40



RECOMMENDATIONS

- Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.
- The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.
- All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.