



# ELF MOTO<sup>2</sup> GOLD

2-stroke motor oil

## KEY DATA

- 2-STROKE MOTOR OIL
- HIGH-QUALITY MINERAL
- INTERNATIONAL STANDARDS
  - ✓ API TC
  - ✓ JASO FB
  - ✓ ISOL-EGB

## APPLICATIONS

ELF MOTO<sup>2</sup> GOLD is a lubricant that is suitable for 2-stroke motorcycles, scooters and mopeds. It is compliant with the API TC, JASO FB and ISO L-EGB international standards.

It is a lubricant that is suitable for relatively un-demanding day-to-day driving conditions. It's composition is perfectly compatible with lead-free fuels. The product is pre-diluted and therefore suitable for separate lubrication and mixing. The oil content needs to be dosed according to the manufacturers' recommendations.

ELF MOTO<sup>2</sup> SELF MIX is a 2-stroke motor oil made using a mineral base. Its increased performance provides standard engines with protection. Exhaust emissions and engine carbon deposits are efficiently controlled.

## CUSTOMER BENEFITS

- **Combustion control:** the strong and efficient detergent additives ensure that the distribution system remains clean. The engine retains its initial efficiency.
- **Reduction in exhaust smoke:** the special solvents and polymers it contains help reduce emissions.
- **Less exhaust smoke at start-up.**

[www.elfmoto.com](http://www.elfmoto.com)



## CHARACTERISTICS\*

Test	Unit	Result
Viscosity grade	-	
Density at 15°C	kg/m <sup>3</sup>	882.5
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	82.5
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	10.6
Viscosity index	-	112
Pour Point	°C	-27
OC Flash Point	°C	160

\*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

## RECOMMENDATIONS FOR USE

Before using the product, the vehicle's user guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

## HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at [www.quickfds.com](http://www.quickfds.com).

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations

TOTAL Oil Asia-Pacific

North Bridge Road

#23-01 Odeon Towers

Singapore 188720

Last update of this datasheet: 06/2020

# ELF MOTO<sup>2</sup> GOLD



Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at [www.elf.sg](http://www.elf.sg)