



CHAINLUB



Lubricant for chains, cables and different mechanisms.

APPLICATIONS

TOTAL CHAINLUB is dedicated to industrial devices and off-road machinery like forklift trucks.

This lubricant is adapted for the lubrication of:

- ✓ Winch, crane and brake cables
- ✓ Joint and various mechanisms (locks, hinges, wipers bearings, dynamos, alternators, domestic devices...)

TOTAL CHAINLUB is designed for hard to reach applications.

PERFORMANCES AND CUSTOMER BENEFITS

TOTAL CHAINLUB exhibits lots of **properties**:

- ✓ Strong stickiness thanks to dedicated additives
- ✓ High penetrating power
- ✓ Good oxidation resistance
- ✓ Anticorrosion properties improved.

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TOTAL CHAINLUB		Method	Value
Density at 15°C	kg/m ³	ISO 3675	821
Kinematic Viscosity at 40°C with solvent	mm ² /s	ISO 3104	5
Kinematic Viscosity at 40°C without solvent	mm ² /s	ISO 3104	68
Flash Point	°C	ISO 2719	> 56

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

CAUTION

Due to the container and the presence of solvents:

- ✓ Keep away from heat, sparks and flame
- ✓ Do not expose to heat and temperatures exceeding 50°C
- ✓ Even when empty, do not puncture or incinerate container.

TOTAL LUBRIFIANTS
 562, avenue du Parc de l'Île
 92029 Nanterre cedex
 FRANCE

TOTAL CHAINLUB
 Update 05/2017
www.lubricants.total.com



This lubricant does not cause adverse health effects when used in the intended application.
 A safety datasheet is accessible on request from your local dealer or on the website www.quickfds.com