



# **DYNATRANS MM**

Transmission Oil

# **KEY DATA**

#### INTERNATIONAL STANDARDS

✓ API GL-4+

✓ Mahindra & Mahindra

#### **APPLICATIONS**

#### **CUSTOMER BENEFITS**

- ###Oc&\|\^} c\\ ![ c\&c\] | And and |\frac{And}{And and and and another and another and all and another another and another another another and another anot
- · High oxidation stability and good thermal resistance helps to extend the oil drain interval
- · Excellent seal comaptability coupled with its good anti-foam characteristics avoids machine brake down

### **CHARACTERISTICS\***

Test	Unit	Test method	DYNATRANS MM
Volumetric mass at 15°C	kg/m <sup>3</sup>	ASTM D 4052	875
Viscosity at 40°C	mm²/s	ASTM D445	92.24
Viscosity at 100°C	mm²/s	ASTM D445	11.32
Flash point	°C	ASTM D92	230
Pour point	°C	ASTM D97	-24

<sup>\*</sup> The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

#### RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

# HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.fr.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.

**DYNATRANS MM** 

Last update of this datasheet: 06/2015

