

according to the Global Harmonized System

SDS #: 089473

RUBIA TIR 7800 15W-40

Issuing date: 2019-06-14

Revision Date: 2019-06-14

Version 1

1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

Product identifier

Product name

RUBIA TIR 7800 15W-40

Other means of identification

Number4QNSubstance/mixtureMixture

Recommended use of the chemical and restrictions on use

Identified uses

Engine oil.

Details of the supplier of the safety data sheet

Supplier

TOTAL OIL ASIA PACIFIC PTE LTD 182 Cecil Street #27-01 Frasers Tower Singapore 069547 Tel: +65 6879 2200 Fax: +65 6879 2203

TOTAL LUBRIFIANTS 562 Avenue du Parc de L'ile 92029 Nanterre Cedex FRANCE Tel: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71

See section 16 for additional information

For further information, please contact:Contact PointHSEE-mail Addressms.ap-sds@total.com

Emergency telephone

Asia-Pacific: +65 3158 1074 Middle-East: +44 1235 239671

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)



according to the Global Harmonized System

SDS #: 089473

RUBIA TIR 7800 15W-40

Issuing date: 2019-06-14

Revision Date: 2019-06-14

Version 1

GHS Label elements, including precautionary statements

None

Signal word

Hazard Statements None

Other hazards which do not result in classification

Physical-Chemical PropertiesContaminated surfaces will be extremely slipperyEnvironmental propertiesThe product may form an oil film on the water surface that may stop the oxygen exchange.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical nature

Mineral oil of petroleum origin

Chemical Name	CAS-No	EC-No	Weight %
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	10-<20
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	10-<20
Phosphorodithioic acid, mixed O,O-bis (2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts	85940-28-9	288-917-4	1-<2.5
Calcium long chain alkylphenate sulphide	122384-87-6	-	1-<2.5
Phenol, (tetrapropenyl) derivs	74499-35-7	616-100-8	0.025-<0.1

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

Description of necessary first-aid measures

General advice

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.



.

.

SAFETY DATA SHEET

according to the Global Harmonized System

SDS # : 089473	RUBIA TIR 7800 15W-40		
Issuing date: 2019-06-14	Revision Date: 2019-06-14 Version		
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.		
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse.		
Inhalation	Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If no breathing, give artificial respiration.		
Ingestion	Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.		
Protection of First-aiders	First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.		
Most important symptoms/effects	, acute and delayed		
Skin contact	Not classified based on available data.		
Eye contact	Not classified based on available data.		
Inhalation	Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.		
Ingestion	Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.		
Indication of immediate medical a	ttention and special treatment needed, if necessary_		
Notes to physician	Treat symptomatically.		
5. FIRE-FIGHTING MEASUR	ES		
Suitable Extinguishing Media			
Suitable Extinguishing Media	Carbon dioxide (CO 2). ABC powder. Foam. Water spray or fog.		
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.		
Specific hazards arising from the	<u>chemical</u>		
Special Hazard	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion products include sulphur oxides (SO2 and SO3) and Hydrogen sulphide H2S, Mercaptar		



. .

SAFETY DATA SHEET

according to the Global Harmonized System

SDS # : 089473	RUBIA TIR 7800 15W-40	
Issuing date: 2019-06-14	Revision Date: 2019-06-14 Version	
	Nitrogen oxides (NOx), Phosphorous oxides, Zinc oxides.	
Advice for fire-fighters		
Special protective equipment for fire-fighters	Wear self-contained breathing apparatus and protective suit.	
Other information	Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.	
6. ACCIDENTAL RELEASE	MEASURES	
Personal precautions, protective e	equipment and emergency procedures	
General Information	Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.	
Environmental precautions		
General Information	Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.	
Methods and material for containn	nent and cleaning up	
Methods for containment	Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials.	
Methods for cleaning up	Dispose of contents/container in accordance with local regulation. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.	
Other information		
Personal Protective Equipment	See Section 8 for more detail.	
Waste treatment	See section 13.	
7. HANDLING AND STORAG	;E	
Precautions for safe handling		
Advice on safe handling	For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.	
Prevention of fire and explosion	Take precautionary measures against static discharges.	



. .

SAFETY DATA SHEET

according to the Global Harmonized System

SDS # : 089473	RUBIA TIR 7800 15W-40	
Issuing date: 2019-06-14	Revision Date: 2019-06-14 Version	
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.	
Conditions for safe storage, incl	uding any incompatibilities_	
Technical measures/Storage conditions	Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidenta emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.	
Materials to Avoid	Strong oxidizing agents.	
8. EXPOSURE CONTROLS	/PERSONAL PROTECTION	
Control parameters		
Exposure limits	Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined).	
Appropriate engineering control	<u>s</u>	
Engineering Measures	Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.	
Individual protection measures,	such as personal protective equipment (PPE)	
Personal Protective Equipment		
General Information	Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers.	
Respiratory protection	None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination	
	Version GHS-AP	



according to the Global Harmonized System

SDS # : 089473	RUBIA TIR 7800 15W-40		
Issuing date: 2019-06-14	Revision Date: 2019-06-14	Version	
	filter for vapour/particulate (EN 14387): Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.		
Eye Protection	If splashes are likely to occur, wear:. Safety glasses with side-shields. EN 166.		
Skin and body protection	Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Type 4/6.		
Hand Protection	Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.		

9. PHYSICAL AND CHEMICAL PROPERTIES

General Information

Appearance Color Physical State @20°C Odor Odor Threshold Important health safety and environmental inform		limpid No information available liquid Characteristic No information available mation _	
Property	<u>Values</u>	<u>Remarks</u>	Method
pH Melting point/range		Not applicable Not applicable	

Boiling point/boiling rangeNo information availableFlash point230 °C
446 °FNo information available

Evaporation rate Flammability Limits in Air

Version GHS-APG

ASTM D92

ASTM D92.

No information available



according to the Global Harmonized System

SDS #: 089473

RUBIA TIR 7800 15W-40

Issuing date: 2019-06-14

Revision Date: 2019-06-14

Version 1

D445

upper Lower Vapor Pressure Vapor density Relative density Density Water solubility Solubility in other solvents logPow	0.8747 874.7 kg/m³	No information available No information available No information available No information available @ 15 °C @ 15 °C Insoluble No information available No information available	
Autoignition temperature Decomposition temperature Viscosity, kinematic	115.8 mm2/s	No information available No information available @ 40 °C	ASTM
Explosive properties Oxidizing Properties Possibility of hazardous reactions	Not explosive Not applicable None under normal	processing	

Other information

Freezing Point

No information available

10. STABILITY AND REACTIVITY

Reactivity	None under normal processing.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks.
Materials to Avoid	Strong oxidizing agents.
Hazardous Decomposition Product	<u>s</u> Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Combustion products include sulphur oxides (SO2 and SO3) and Hydrogen sulphide H2S, Mercaptans, Nitrogen oxides (NOx), Phosphorous oxides, Zinc oxides.

11. TOXICOLOGICAL INFORMATION

Version GHS-APG



according to the Global Harmonized System

RUBIA TIR 7800 15W-40

Issuing date: 2019-06-14

Revision Date: 2019-06-14

Version 1

Information on likely routes of exposure

Inhalation	Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Skin contact	Not classified based on available data.
Eye contact	Not classified based on available data.
Symptoms related to the physical, chemical and toxicological characteristics	
Symptoms	No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure_

Acute toxicity - Product Information

Oral Not classified based on available data. 0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

Dermal Not classified based on available data. 0 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

Inhalation Not classified based on available data.

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated	LD50 > 5000 mg/kg bw (rat - OECD	LD50 > 5000 mg/kg bw (rabbit -	LC50 (4h) > 5 mg/l (aerosol) (rat -
heavy paraffinic	420)	OECD 402)	OECD 403)
Distillates (petroleum), hydrotreated	LD50 > 5000 mg/kg bw (rat - OECD	LD50 > 5000 mg/kg bw (rabbit -	LC50 (4h) > 5 mg/l (aerosol) (rat -
light paraffinic	420)	OECD 402)	OECD 403)
Phosphorodithioic acid, mixed	LD50 3080 mg/kg bw (rat - OECD	LD50 20000 mg/kg bw (rabbit -	
O,O-bis (2-ethylhexyl and iso-Bu	401)	OECD 402)	
and iso-Pr) esters, zinc salts			
Calcium long chain alkylphenate	LD50 > 5000 mg/kg (Rat)	LD50 > 2000 mg/kg (Rabbit)	
sulphide			
Phenol, (tetrapropenyl) derivs	LD50 >2000 mg/kg (rat)	LD50 >2000 mg/kg (rat)	

Skin corrosion/irritation

Not classified based on available data. The supplier of one or more of the components contained within this formulation has indicated that he has data on the components and/or similar mixtures, which confirms that at the concentration used, classification is not required.



according to the Global Harmonized System

SDS # : 089473	RUBIA TIR 7800 15W-40
Issuing date: 2019-06-14	Revision Date: 2019-06-14 Version 1
Serious eye damage/eye irritation	Not classified based on available data. The supplier of one or more of the components contained within this formulation has indicated that he has data on the components and/or similar mixtures, which confirms that at the concentration used, classification is not required.
Sensitization	Not classified based on available data.
Carcinogenicity	Not classified based on available data. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.
Germ Cell Mutagenicity	Not classified based on available data.
Reproductive toxicity	Not classified based on available data.
Target Organ Effects (STOT)	None known.
STOT - single exposure	Not classified based on available data.
STOT - repeated exposure	Not classified based on available data.
Aspiration hazard	Not classified based on available data.
Other adverse effects	Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

12. ECOLOGICAL INFORMATION

Ecotoxicity

Not classified based on available data. This product contains one or more components that have a branched alkylphenol impurity which is very toxic to aquatic life (disclosed in section 3). Components containing the impurity have been tested and are not toxic to aquatic life. Therefore, the data in Section 3 for the alkylphenol impurity should not be used to classify the product for aquatic toxicity.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and	Toxicity to fish	Toxicity to
		other aquatic invertebrates		microorganisms



according to the Global Harmonized System

SDS # : 089473

RUBIA TIR 7800 15W-40

Issuing date: 2019-06-14

Revision Date: 2019-06-14

Version 1

Distillates (petroleum), hydrotreated heavy	EL50 (48h) > 100 mg/l (Pseudokirchnerella	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss -	
paraffinic 64742-54-7	subcapitata - OECD 201)	(Daprinia magna - OECD 202)	OECD 203)	
Distillates (petroleum),	EL50 (48h) > 100 mg	EL50 (48h) > 10000 mg/l	LL50 (96h) > 100 mg/l	
hydrotreated light paraffinic	(Pseudokirchnerella	(Daphnia magna - OECD	(Oncorhynchus mykiss -	
64742-55-8	subcapitata - OECD 201)	202)	OECD 203)	
Calcium long chain	EC50 (72h) 1000 mg/l			
alkylphenate sulphide	(Algae - WAF)			
122384-87-6				

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Distillates (petroleum), hydrotreated light paraffinic 64742-55-8		NOEL (21d) 10 mg/l (Daphnia magna - OECD 211)	NOEL (14/21d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	

Effects on terrestrial organisms No information available.

Persistence and degradability

No information available.

Bioaccumulative potential

Product Information	No information available.
logPow	No information available

Component Information No information available

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic - 64742-54-7	-

<u>Mobility</u>



according to the Global Harmonized System

SDS # : 089473	RUBIA TIR 7800 15W-40	
Issuing date: 2019-06-14	Revision Date: 2019-06-14 Version	
Soil	Given its physical and chemical characteristics, the product generally shows low soil mobility.	
Air Water	Loss by evaporation is limited. The product is insoluble and floats on water.	
Other adverse effects		
General Information	No information available.	
13. DISPOSAL CONSIDERA	TIONS	
Waste from Residues / Unused Products	Should not be released into the environment. Do not empty into drains. Dispose of in accordance with all applicable national environmental laws and regulations. Where possible recycling is preferred to disposal or incineration.	

Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
Other information	Refer to section 8 for safety and protective measures for disposal personnel.

14. TRANSPORT INFORMATION

ADR/RID	Not regulated
IMDG/IMO	Not regulated
	Not regulated
ADN	Not regulated

15. REGULATORY INFORMATION

Further information

No information available

National regulatory information

No information available

.



according to the Global Harmonized System

SDS # : 089473

RUBIA TIR 7800 15W-40

Issuing date: 2019-06-14

Revision Date: 2019-06-14

Version 1

16. OTHER INFORMATION

Issuing date: Revision Date: Revision Note 2019-06-14 2019-06-14 No information available.

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists bw = body weight bw/day = body weight/day EC x = Effect Concentration associated with x% response GLP = Good Laboratory Practice IARC = International Agency for Research of Cancer LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals LL = Lethal Loading NIOSH = National Institute of Occupational Safety and Health NOAEL = No Observed Adverse Effect Level NOEC = No Observed Effect Concentration NOEL = No Observed Effect Level OECD = Organization for Economic Co-operation and Development OSHA = Occupational Safety and Health Administration UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material Legend Section 8 ACGIH - American Conference of Governmental Industrial Hygienists TWA - Time Weight Average STEL - Short Term Exposure Limits S* - Skin notation Ceiling: Maximum limit value

Additional details on the supplier of the product

U.A.E Supplier	TOTAL MARKETING MIDDLE EAST FZE Burjuman Business Tower, 11th Floor Sheikh Khalifa Bin Zayed Road Dubai P.O. Box 14871 U.A.E Tel: +971 4 709 50 00 Fax: +971 4 351 91 54	CAMBODIA Supplier	TOTAL CAMBODGE ANINA Building 6th Floor, No 240, St. 271, B.P600, 12351 Phnom Penh, Cambodia Tel: +855 23 218 630 Fax: +855 23 217 662
INDIA Supplier	TOTAL OIL INDIA PVT. LTD. 3rd Floor, The Leela Galleria, Andheri - Kurla Road, Andheri (East), Mumbai Maharashtra State, INDIA 400059 Tel: +91 22 6723 2500 Fax: +91 22 6723 2600	JORDAN Supplier	TOTAL JORDAN Reem Center, 4th Floor 244 Arar Street, Wadi Saqra P.O. Box 831285, Amman 11183 Jordan Tel: +962 6 500 80 05 Fax: +962 6 500 80 08



according to the Global Harmonized System

SDS #: 089473

RUBIA TIR 7800 15W-40

Issuing date: 2019-06-14

Revision Date: 2019-06-14

Version 1

LEBANON Supplie	r TOTAL LIBAN Rue Achrafieh, Imm. Tilal Bloc B, 2ème Etage B.P. 11-3636 Beyrouth - Liban Tel : + 961 1 21 22 50 Fax: + 961 1 21 21 33	PAKISTAN Supplie	r TOTAL PARCO PAKISTAN LTD 10 Tariq Block, New Garden Town Lahore 54700, Pakistan Tel: +92 42 111 709 709 Fax: +92 42 354 683 66
PAPUA NEW GUINEA Supplier	TOTAL OIL ASIA PACIFIC PTE LTD - PNG Cuthbertson Street Level 4, Cuthbertson House PO BOX 1784 Port Moresby Papua New Guinea Tel: +675 320 2141 Fax: +675 320 3951	SAUDI ARABIA Supplier	SAUDI TOTAL PETROLEUM PRODUCTS CO. LTD 704, Zahran Business Center Sultan street - Tower A , 7th floor PO Box 4861, Jeddah 21463 K.S.A Tel: +966 12 22 56 300 Fax: +966 12 22 56 311

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet