

TOTAL QUARTZ 7000 SN 10W-40

Engine Oil

KEY DATA

LIGHT VEHICLE RANGE



GASOLINE & DIESEL ENGINE OIL
SAE 10W-40
SYNTHETIC TECHNOLOGY



INTERNATIONAL STANDARDS

- API SN/CF
- Backward compatible API SM, SL, SJ / CF

TECHNOLOGY

Clean-Shield technology

The effective engine cleaning technology.

Thanks to advanced detergent molecules designed to capture and isolate dirt such as sludge and soots, Clean Shield technology keeps engines clean in the long term.

Fighting against this major cause of breakdowns, TOTAL QUARTZ with Clean Shield technology is the oil of choice across the globe to guarantee engine cleanliness during the entire drain interval and after oil change.



APPLICATIONS

TOTAL QUARTZ 7000 SN is high performance multi-grade oil for passenger cars, designed to exceed the latest API SN/CF sequence.

The synthetic technology formulation brings significant improvement of all properties compared to mineral engine oils: engine protection against wear and deposits, performances, oil drain intervals and overall driving experience.

This product has been developed for both gasoline and diesel engines not equipped with diesel particulate filters (passenger cars and light industrial vehicles). It can be used for various operating conditions (city traffic, road, motorways), and in all seasons.

This exceeds the latest API SN specifications and is fully backward compatible with all previous sequences (API MS, SL...).

CUSTOMERS BENEFITS

- Engine oil enhancing all engine performances.
- Outstanding long-term wear protection of all engine parts (distribution, rings, pistons, and liner) increasing overall engine life.
- These engine oils can be used for a wide variety of car manufacturers.
- Extended oil change intervals compared to standard engine oils.
- Reinforced thermal and oxidation stability.

CHARACTERISTICS²

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	10W-40
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	93.1
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	14.1
Density at 15°C	kg/m ³	ASTM D1298	866
Viscosity index	-	ASTM D2270	155
Pour point	°C	ASTM D97	-30
OC Flash point	°C	ASTM D92	232

² The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <http://sdstotalms.total.com>.

This product should not be used for any purposes other than the ones for which it is intended.

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

TOTAL QUARTZ 7000 SN 10W-40
Last update of this datasheet: 09/2020

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at www.lubricants.total.com.