



# AGRIMOT ULTRATEC 10W-40

Very high performance lubricant for Diesel engines based upon a synthetic technology.

## Applications

Loaded Diesel engines  
Phases I, II or IIIa

Particularly suitable for the lubrication of the latest generation of Diesel engines developed by European manufacturers.

New generation synthetic technology lubricant for all types of Diesel engines, turbo-charged or naturally aspirated, which are found on agricultural vehicles.

Can handle the most severe applications.

## Performances



Classifications: **ACEA E4 / E7 / E5 • API CF**

Manufacturers approvals: **Daimler MB-Approval 228.5 • DEUTZ DQC III-10 • MAN M 3277**

## Customer benefits

Security under loaded  
Conditions

Recommended by all European engine manufacturers in case of severe working conditions.

Easier cold start.

Technical performances

Exceptional anti wear and detergency properties.

Excellent service stability.

Excellent dispersive, anti-oxidant and anti-corrosion properties.

Outstanding performances due to the lubricant's synthetic basis added to high performance additives.

## Characteristics\*

AGRIMOT ULTRATEC 10W-40	Units	Value
Kinematic viscosity at 40° C	mm <sup>2</sup> /s	85
Kinematic viscosity at 100° C	mm <sup>2</sup> /s	13.1
Viscosity index	-	157
Pour point	° C	-42

\* The typical characteristics mentioned represent mean values

**AGRIMOT ULTRATEC 10W-40 Sheet updated 06/2015** – Developed with **TOTAL** technology at the service of **CLAAS**

This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.

**CLAAS**

