



MTC 100 – 150 - 220



Loss lubrication of chainsaw and high speed machinery

APPLICATIONS

TOTAL MTC 100 – 150 – 220 is dedicated to all **high speed machineries**: manual or mechanical chainsaw, chain conveyors.

This lubricant is adapted to **all wood transformation**.

SAE 100 grade is mainly adapted to the **lubrication of mechanical chainsaw** installed in wood cutting machines.

SAE 150 and 220 grades are particularly recommended for **manual chainsaw** of woodcutter and also for industrial conveyors.

PERFORMANCES AND CUSTOMER BENEFITS

TOTAL MTC 100 – 150 – 220 has very **adhesive behaviour** which reduces spattering and guarantees the lubrication on the entire length of the moving chain.

TOTAL MTC 100 – 150 – 220 exhibits lots of **properties**:

- ✓ Reinforced anti-wear additivation
- ✓ Improved anti-rust property
- ✓ Friction reduction
- ✓ Chain and guide wear reduction
- ✓ Spattering, pollution and oil consumption reductions

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TOTAL MTC		Method	100	150	220
Density at 15°C	kg/m ³	ASTM D1298	883	879	884
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	100	150	220
Pour Point	°C	ASTM D97	-15	-12	-9
Behaviour	-	-	Adhesive	Adhesive	Adhesive

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

TOTAL LUBRIFIANTS
562, avenue du Parc de l'Île
92029 Nanterre cedex
FRANCE

TOTAL MTC 100 – 150 – 220
Update 09/2014
www.lubricants.total.com



This lubricant does not cause adverse health effects when used in the intended application.
A safety datasheet is accessible on request from your local dealer or on the website www.quickfds.com