



RUBIA MINI 15W40 TOTAL

Value for money lubricant designed for naturally aspirated and turbo charged diesel engines

APPLICATIONS

- For all naturally aspirated and turbo charged diesel engine operating under varied condition
- Can be used for light commercial vehicles and pickup vans

SPECIFICATION

- API CF4/SG
- MACK T8A
- EDL 3

ADVANTAGES

- Excellent oxidation resistance helps in better deposit and sludge control.
- Speciality additivation avoids cracking of oil and control soot accumulation thus ensuring proper lubrication during hot summer
- Polymer infusion helps in having faster fluidity at cold temperature and desired film thickness at hot temperature to give proper lubrication thus reduces wastage of power
- Built in anti wear characteristics protects the engine most sensitive parts from wear and seizure

| TYPICAL CHARACTERISTICS | TEST METHOD ASTM | RUBIA MINI 15W-40 |
|-----------------------------------|---------------------|----------------------|
| Density at 29.5°C, kg/l | D 4052 | 0.8648 |
| Kinematic viscosity at 100°C, cSt | D 445 | 14.54 |
| Viscosity Index | D 2270 | 136 |
| Pour point, °C | D 97 | -27 |
| Total Base Number, mg KOH/g | D 2896 (B) | 6.9 |
| Flash point COC, °C | D 92 | 242 |

(Above characteristics are mean values given as an information)

TOTAL OIL INDIA PVT LTD.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059. Tel. : 022 66407700 Fax : 022 66407720
Regional Offices : Chennai Tel. 044 28412790/28412823, Mumbai Tel. 022 25705775/6/7, Noida Tel. 0120 2516794/5/6,
Kolkata Tel No. : 033 66228200 / 8209. Fax No. : 033 66228212.

All reasonable care has been taken to ensure that the information provided here is accurate as of date of printing. However due to continual product development, the information contained herein is subjected to change without notification. MSDS can be obtained from our local representative or can be down loaded from : www.total.co.in

Date 01/12