



TOTAL FINASOL WR

Solvent Based Degreaser

KEY DATA

FINASOL WR is a blend of high aromatic solvents and effective surfactant soaps resulting in an effective general-purpose water rinseable solvent capable of cutting through tough to remove grease and grime.

Quick Break formulation: readily separates water and oil.

Ready to use, apply undiluted by brush or spray then hose off.

NOTE: Can be detrimental to paint finishes where there is old or damaged paintwork.

Customer benefits

- ✓ Wide range of uses for degreasing and cleaning in workshops for automotive, heavy industry and mining.
- ✓ Easy to use: Simply apply undiluted with a brush or spray, allow 1 to 2 minutes for FINASOL WR to penetrate and begin to lift the grease and grime then hose off. For best result hose off using a high-pressure water spray.
- ✓ Effective Formulation that readily emulsifies and then breaks the emulsion at a high rate making it suitable where triple interceptors are in use.

Characteristics*

Test	Result
Appearance	Pale Green Liquid
Specific gravity	0.82
Flash Point	< 60.5 deg C
Flammable	Class 3 Flammable under ADG Code
Solubility	Emulsifies

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

Recommendations for use

Before using the product, the vehicle's maintenance guide should be checked.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

Health, safety and the environment

Please refer to the Material Safety Data Sheet for full safety information. This can be obtained on request from your local reseller and is available for consultation at <u>http://www.totaloil.com.au/</u>.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.

TOTAL OIL AUSTRALIA PTY LTD Bourke Place Level 23, 600 Bourke St Melbourne VIC 3000 Australia

TOTAL FINASOL WR

Last update of this datasheet: 02/2021

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at <u>http://www.totaloil.com.au/</u>.