

Hi-Perf 4T Special 10W-30



Premium Mineral

APPLICATIONS

4-stroke motorcycle engine oil

TOTAL Hi-Perf 4T Special 10W-30 is a lubricant that is particularly recommended for all types of 4-stroke engine motorcycles, with manual gear operation.

The product is in compliance with the API SN and JASO MA2 international standards.

It is perfectly compatible with catalytic converters. The oil change intervals recommended by the constructors and the minimum required viscosities must be complied with. This lubricant is compatible with lead-free fuels.

PERFORMANCES

Premium Mineral

API SN
JASO MA2

CUSTOMER BENEFITS

TOTAL Hi-perf 4T Special 10W-30 is specially designed to operate efficiently under extreme conditions. Its exclusive and unique formulation does not let the oil film break easily, thereby providing superior protection even in heavy traffic 'stop-n-go' conditions. This leads to a distinctly superior performance, which can be felt from the first use itself!

- **Active prevention of friction:** Piston and ring sealing is ensured along with reduction of deposits. This leads to lower oil consumption and prevents loss of compression and loss of power. Thus the users get a smooth ride.
- Eliminates 'aeration' of lubricant by preventing foam formation and consequently avoids early wear and tear
- **Superior gear protection:** the special additives in the oil stick for long to the gear parts preventing metal-to-metal contact under high pressure conditions and also during frequent gear changes.
- The oil formulation is certified with the latest JASO MA2 specifications, thus preventing clutch slippage at start-up and varying speeds
- **HTHS viscosity:** The anti-wear properties give the oil a High Temperature High Shear viscosity. This gives users ideal performance under extreme pressure conditions. Engine is protected by optimal maintenance of oil film thickness even in the most extreme load or speed conditions

CHARACTERISTICS

	Method	Units	
Volumetric mass at 15°C	ASTM D1298	kg/m ³	865.6
Viscosity at 40°C	ASTM D445	mm ² /s	74.2
Viscosity at 100°C	ASTM D445	mm ² /s	11.2
Viscosity Index	ASTM D2270	-	146
Pour Point	ASTM D97	°C	-33
Flash Point	ASTM D92	°C	240

The typical characteristics mentioned represent mean values.

TOTAL Oil Asia-Pacific

Total
Version December 2012



This lubricant, when used according to our recommendations and for the purpose for which is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.