



High performance fluid for continuously variable transmission (CVT) of passenger cars

PERFORMANCES LEVELS

OEM-Approved

- ✓ Renault CVT FK/CK/DK

APPLICATIONS

- ELFMATIC CVT is recommended for RENAULT CVT Transmissions
- ELFMATIC CVT is recommended for JATCO CVT Transmissions
- Do not use another CVT fluid for Renault Application
- Do not use this fluid for NISSAN CVT NS-1
- This oil is compatible with NISSAN CVT NS-2

CUSTOMER BENEFITS

- Very good **thermal and oxidation stability**
- **Very high cold fluidity**
- Ensures very **good shifting** at all temperatures.
- Very **high resistance to shear**.
- **Protection** against wear

PHYSICAL AND CHEMICAL CHARACTERISTICS

ELFMATIC CVT MV	Unit	Method	Value
Colour	-	ASTM D1500	Green
Density at 15°C	kg/m ³	ASTM D4052	847
Kinematic Viscosity at 40 °C	mm ² /s	ASTM D445	26
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	6.2
Brookfield Viscosity at -40°C	cP	ASTM D2983	5800
Viscosity Index	-	ASTM D2270	204
Pour Point	°C	ASTM D97	-48
Flash Point	°C	ASTM D92	172

The features mentioned above are average values obtained with some variability in production and do not constitute a specification.