



**Very high performance lubricant using ELF synthetics technology. Intended for lubricating passenger cars Gasoline and Diesel engines.**

## APPLICATIONS

- |  |   |
|--|---|
| <b>Most recent technology engines</b>          | • Suitable for all gasoline and diesel engines, particularly for most recent ones.  |
| <b>The most severe journeys</b>                | • Suitable for all journeys (in town, on highways and motorways) and particularly in severe conditions.   |
| <b>« Vigorous » driving, all times of year</b> | • For all driving styles, particularly « vigorous » and high speeds.<br>• Meets the needs of the motor manufacturers regarding extended oil change intervals. |

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

## PERFORMANCES

|                                     |   |            |                    |         |     |               |                   |         |               |
|-------------------------------------|---|------------|--------------------|---------|-----|---------------|-------------------|---------|---------------|
| <b>International specifications</b> | ACEA : A3/B4<br>API: SN/CF  |            |                    |         |     |               |                   |         |               |
| <b>OEMs approvals</b>               | <table border="0"> <tr> <td>VOLKSWAGEN</td> <td>VW 502.00 / 505.00</td> </tr> <tr> <td>PORSCHE</td> <td>A40</td> </tr> <tr> <td>MERCEDES BENZ</td> <td>MB-Approval 229.5</td> </tr> <tr> <td>RENAULT</td> <td>RN0700/RN0710</td> </tr> </table> <p>Meets the requirements of: FIAT 9.55535-M2 / CHRYSLER MS-12991</p> | VOLKSWAGEN | VW 502.00 / 505.00 | PORSCHE | A40 | MERCEDES BENZ | MB-Approval 229.5 | RENAULT | RN0700/RN0710 |
| VOLKSWAGEN                          | VW 502.00 / 505.00  |            |                    |         |     |               |                   |         |               |
| PORSCHE                             | A40   |            |                    |         |     |               |                   |         |               |
| MERCEDES BENZ                       | MB-Approval 229.5   |            |                    |         |     |               |                   |         |               |
| RENAULT                             | RN0700/RN0710   |            |                    |         |     |               |                   |         |               |

## CUSTOMER BENEFITS

- |  |  |
|--|--|
| <b>Optimal performance</b>                         | • Excellent engine protection, particularly against timing system wear.                                    |
| <b>Excellent engine cleanliness and protection</b> | • Ensures maximum engine cleanliness.  |
| <b>Lengthens engine life</b>                       | • Outstanding thermal stability, oxidation resistance eliminating any degradation even in very severe use. |
| <b>Facilitates cold starts</b>                     | • Immediate lubrication of engine parts during cold starts, leading to longer engine life.                 |
| <b>Extended oil change intervals</b>               | • Meets the requirements of the manufacturers as regards extended oil change intervals.                    |

## CHARACTERISTICS

|                    | Method     | Units              | SAE Grade 5W-40 |
|--------------------|------------|--------------------|-----------------|
| Viscosity at 40°C  | ASTM D445  | mm <sup>2</sup> /s | 90              |
| Viscosity at 100°C | ASTM D445  | mm <sup>2</sup> /s | 14,7            |
| Viscosity index    | ASTM D2270 | -                  | 172             |
| Pour point         | ASTM D97   | °C                 | - 42            |
| Flash point        | ASTM D92   | °C                 | 230             |
| B.N.               | ASTM D2896 | mgKOH/g            | 10              |

The typical characteristics mentioned represent mean values