

according to the Global Harmonized System

SDS # : 082513

ATF III

Issuing date: 2018-02-02

Revision Date: 2019-05-15

Version 1.01

1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

| Product identifier | |
|--|---|
| Product name | ATF III |
| Other means of identification | |
| Number Substance/mixture | OP4 Mixture |
| Recommended use of the chemical | and restrictions on use |
| ldentified uses Uses advised against | Automatic transmission fluids. Do not use for any purpose other than the one for which it is intended. |
| Details of the supplier of the safety | data sheet |
| Supplier | TOTAL OIL ASIA PACIFIC PTE LTD 182 Cecil Street #27-01 Frasers Tower Singapore 069547 Tel: +65 6879 2200 Fax: +65 6879 2203 TOTAL LUBRIFIANTS 562 Avenue du Parc de L'ile 92029 Nanterre Cedex FRANCE Tel: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71 See section 16 for additional information |
| For further information, please con Contact Point E-mail Address | tact: HSE ms.ap-sds@total.com |
| Emergency telephone | |
| Asia-Pacific: +65 3158 1074 Middle-East: +44 1235 239671 | |

2. HAZARDS IDENTIFICATION

.

Classification of the substance or mixture



according to the Global Harmonized System

| SDS # : 082513 | AI | FIII | |
|---------------------------|--|-------------------------|-------------|
| Issuing date: 2018-02-02 | 2 Revision Date: | 2019-05-15 | Version 1.0 |
| Not a hazardous substanc | e or mixture according to the Globally | Harmonized System (GHS) | |
| GHS Label elements, inc | luding precautionary statements | | |
| Signal word | None | | |
| Hazard Statements None | | | |

Physical-Chemical PropertiesContaminated surfaces will be extremely slipperyEnvironmental propertiesThe product may form an oil film on the water surface that may stop the oxygen exchange.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical nature

Mineral oil of petroleum origin

| Chemical Name | CAS-No | EC-No | Weight % |
|---|------------|-----------|------------|
| Lubricating oils (petroleum), C20-50, | 72623-87-1 | 276-738-4 | 90-<100 |
| hydrotreated neutral oil-based | | | |
| Methacrylate copolymer | ^ | - | 1-<3 |
| Alkoxylated long chain alkylamine | ^ | 620-540-6 | 0.025-<0.1 |
| 2-(2-heptadec-8-enyl-2-imidazolin-1-yl) | 95-38-5 | 202-414-9 | 0.025-<0.1 |
| ethanol | | | |

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

Description of necessary first-aid measures

| General advice | IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE. |
|----------------|--|
| Eye contact | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. |
| Skin contact | Wash off immediately with soap and plenty of water while removing all contaminated |

Version GHS-APG



.

.

SAFETY DATA SHEET

according to the Global Harmonized System

| SDS # : 082513 | ATF III | |
|-----------------------------------|--|--------------------|
| Issuing date: 2018-02-02 | Revision Date: 2019-05-15 Version | n 1.0 ⁻ |
| | clothes and shoes. Wash contaminated clothing before reuse. High pressure jets may cause skin damage. Take victim immediately to hospital. | у У |
| Inhalation | Remove casualty to fresh air and keep at rest in a position comfortable for breathing. breathing, give artificial respiration. | lf not |
| Ingestion | Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to a unconscious person. Call a physician or Poison Control Center immediately. | n |
| Protection of First-aiders | First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other prop respiratory medical device. | er |
| Most important symptoms/effects | s, acute and delayed | |
| Skin contact | Not classified based on available data. High pressure injection of the products under t skin may have very serious consequences even though no symptom or injury may be apparent. | |
| Eye contact | Not classified based on available data. | |
| Inhalation | Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system. | |
| Ingestion | Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. | |
| Indication of immediate medical a | attention and special treatment needed, if necessary | |
| Notes to physician | Treat symptomatically. | |
| 5. FIRE-FIGHTING MEASUR | RES | |
| Suitable Extinguishing Media | | |
| Suitable Extinguishing Media | Carbon dioxide (CO 2). ABC powder. Foam. Water spray or fog. | |
| Unsuitable Extinguishing Media | Do not use a solid water stream as it may scatter and spread fire. | |
| Specific hazards arising from the | chemical | |
| Special Hazard | Incomplete combustion and thermolysis may produce gases of varying toxicity such a carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These be highly dangerous if inhaled in confined spaces or at high concentration. Combusti products include sulphur oxides (SO2 and SO3) and Hydrogen sulphide H2S, Nitrog oxides (NOx), Mercaptans. | may on |



Hygiene measures

.

.

SAFETY DATA SHEET

according to the Global Harmonized System

| SDS # : 082513 | ATF III |
|---|--|
| Issuing date: 2018-02-02 | Revision Date: 2019-05-15 Version 1.0 |
| Advice for fire-fighters | |
| Special protective equipment for fire-fighters | Wear self-contained breathing apparatus and protective suit. |
| Other information | Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| 6. ACCIDENTAL RELEASE | MEASURES |
| Personal precautions, protective e | quipment and emergency procedures |
| General Information | Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. |
| Environmental precautions | |
| General Information | Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained. |
| Methods and material for containn | nent and cleaning up |
| Methods for containment | Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials. |
| Methods for cleaning up | Dispose of contents/container in accordance with local regulation. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations. |
| Other information | |
| Personal Protective Equipment | See Section 8 for more detail. |
| Waste treatment | See section 13. |
| 7. HANDLING AND STORAG | E |
| Precautions for safe handling | |
| Advice on safe handling | For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. |
| Provention of fire and evaluation | Take proceutionany modeuros against static discharges |



.

.

SAFETY DATA SHEET

according to the Global Harmonized System

| SDS #: 082513 ATF III | | |
|---------------------------------------|---|--|
| Issuing date: 2018-02-02 | Revision Date: 2019-05-15 Version 1. | |
| | contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. | |
| Conditions for safe storage, incl | uding any incompatibilities | |
| Technical measures/Storage conditions | Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels o the containers (even if they are empty). Design the installations in order to avoid accident emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture. | |
| Materials to Avoid | Strong oxidizing agents. | |
| 8. EXPOSURE CONTROLS | /PERSONAL PROTECTION | |
| Control parameters | | |
| Exposure limits | Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined). | |
| Appropriate engineering control | <u>s</u> | |
| Engineering Measures | Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tank containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment. | |
| Individual protection measures, | such as personal protective equipment (PPE) | |
| Personal Protective Equipment | | |
| General Information | Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers. | |
| Respiratory protection | None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387): Type A/P1. Warning ! filters have a limited use | |



according to the Global Harmonized System

| SDS # : 082513 | ATF III | |
|--------------------------|--|--|
| Issuing date: 2018-02-02 | Revision Date: 2019-05-15 | Version 1.01 |
| | duration. The use of breathing apparatus must comply strictly with the instructions and the regulations governing their choices and uses. | manufacturer's |
| Eye Protection | If splashes are likely to occur, wear:. Safety glasses with side-shields. | EN 166. |
| Skin and body protection | Wear suitable protective clothing. Protective shoes or boots. Long slee 4/6. | ved clothing. Type |
| Hand Protection | Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. In case of with the product, it is recommended to wear gloves complying with EN standards, protecting at least for 480 minutes and having a thickness of These values are indicative only. The level of protection is provided by glove, its technical characteristics, its resistance to the chemicals to be appropriateness of its use and its replacement frequency. Please obse regarding permeability and breakthrough time which are provided by th gloves. Also take into consideration the specific local conditions under used, such as the danger of cuts, abrasion, and the contact time. | 420 and EN 374 of 0,38 mm at least. v the material of the e handled, the erve the instructions he supplier of the |

9. PHYSICAL AND CHEMICAL PROPERTIES

General Information

.

| Appearance | limpid |
|----------------------|--------------------------|
| Color | red |
| Physical State @20°C | liquid |
| Odor | No information available |
| Odor Threshold | No information available |

Important health safety and environmental information

| Property | <u>Values</u> | <u>Remarks</u> | <u>Method</u> |
|-----------------------------|-------------------------|--|---|
| pH Melting point/range | | Not applicable Not applicable | |
| Boiling point/boiling range | | No information available | |
| Flash point | 212 °C 414 °F | | Cleveland Open Cup (COC) Cleveland Open Cup (COC). |
| Evaporation rate | | No information available | |
| Flammability Limits in Air | | No information available | |
| upper Lower | | No information available No information available | |



according to the Global Harmonized System

SDS # : 082513

ATF III

Issuing date: 2018-02-02

Revision Date: 2019-05-15

Version 1.01

| Vapor Pressure Vapor density Relative density Density Water solubility Solubility in other solvents logPow | 0.8461 846.1 kg/m ³ | No information available No information available @ 15 °C @ 15 °C Insoluble No information available No information available | ASTM D 4052 ASTM D 4052 | |
|--|---|---|----------------------------|--|
| Autoignition temperature Decomposition temperature Viscosity, kinematic | 32.58 mm2/s 7.272 mm2/s | No information available No information available @ 40 °C @ 100 °C | ISO 3104 ISO 3104 | |
| Explosive properties Oxidizing Properties Possibility of hazardous reactions | Not explosive Not applicable None under normal processing | | | |
| Other information | | | | |
| Freezing Point | | No information available | | |

| 10. STABILITY AND REACTIVITY | |
|---|---|
| Reactivity | None under normal processing. |
| Chemical stability | Stable under recommended storage conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks. |
| Materials to Avoid | Strong oxidizing agents. |
| Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Combustion products include sulphur oxides (SO2 and SO3) and Hydrogen sulphide H2S, Mercaptans Nitrogen oxides (NOx). | |

11. TOXICOLOGICAL INFORMATION

.

Information on likely routes of exposure

.



according to the Global Harmonized System

| ATF III | | | | | |
|--|---|---|---|--|--|
| Issuing date: 2018-02-02 | Revision Date: 2019-05-15 Version | | | | |
| Inhalation | | Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system. | | | |
| Ingestion | | Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. | | | |
| Skin contact | | Not classified based on available data. High pressure injection of the products under the skin may have very serious consequences even though no symptom or injury may be apparent. | | | |
| Eye contact | Not classified based on ava | ailable data. | | | |
| Symptoms related to the physic | ical, chemical and toxicological | characteristics | | | |
| Symptoms | No information available. | | | | |
| Acute toxicity - Product Inform Oral | Not classified based on ava | | | | |
| Dermal | gredient(s) of unknown acute oral Not classified based on ava of ingredient(s) of unknown acute | ailable data. | | | |
| Inhalation | Not classified based on ava | Not classified based on available data. | | | |
| | | | | | |
| Acute toxicity - Component In | formation | | | | |
| Acute toxicity - Component In Chemical Name | formation | LD50 Dermal | LC50 Inhalation | | |
| Chemical Name Lubricating oils (petroleum), C20-50, hydrotreated neutral | r | LD50 Dermal LD50 > 5000 mg/kg bw (rabbit - OECD 402) | LC50 Inhalation LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403) | | |
| Chemical Name Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Methacrylate copolymer | LD50 Oral LD50 > 5000 mg/kg bw (rat - OECD 401) LD50 >2000 mg/kg (rat) | LD50 > 5000 mg/kg bw (rabbit - | LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403) LC50 >5.2 mg/l | | |
| Chemical Name Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Methacrylate copolymer Alkoxylated long chain alkylamine | LD50 Oral LD50 > 5000 mg/kg bw (rat - OECD 401) LD50 >2000 mg/kg (rat) LD50 300-2000 mg/kg (Rat) | LD50 > 5000 mg/kg bw (rabbit - OECD 402) LD50 >2000 mg/kg (rabbit) | LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403) | | |
| Chemical Name Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Methacrylate copolymer Alkoxylated long chain alkylamine | LD50 Oral LD50 > 5000 mg/kg bw (rat - OECD 401) LD50 >2000 mg/kg (rat) | LD50 > 5000 mg/kg bw (rabbit - OECD 402) | LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403) LC50 >5.2 mg/l | | |
| Chemical Name Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Methacrylate copolymer Alkoxylated long chain alkylamine 2-(2-heptadec-8-enyl-2-imidazolin-1 | LD50 Oral LD50 > 5000 mg/kg bw (rat - OECD 401) LD50 >2000 mg/kg (rat) LD50 300-2000 mg/kg (Rat) | LD50 > 5000 mg/kg bw (rabbit - OECD 402) LD50 >2000 mg/kg (rabbit) LD50 > 2000 mg/kg (Rat) | LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403) LC50 >5.2 mg/l | | |
| Chemical Name Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Methacrylate copolymer Alkoxylated long chain alkylamine 2-(2-heptadec-8-enyl-2-imidazolin-1 -yl)ethanol | LD50 Oral LD50 > 5000 mg/kg bw (rat - OECD 401) LD50 >2000 mg/kg (rat) LD50 300-2000 mg/kg (Rat) LD50 1265 mg/kg (Rat - OECD 401) Not classified based on ava | LD50 > 5000 mg/kg bw (rabbit - OECD 402) LD50 >2000 mg/kg (rabbit) LD50 > 2000 mg/kg (Rat) ailable data. | LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403) LC50 >5.2 mg/l | | |

Carcinogenicity Not classified based on available data

.

.



according to the Global Harmonized System

| ATF III | |
|---|--|
| Revision Date: 2019-05-15 | Version 1.01 |
| | |
| Not classified based on available data | |
| Not classified based on available data. | |
| None known | |
| | Revision Date: 2019-05-15 Not classified based on available data Not classified based on available data. |

STOT - single exposureNot classified based on available dataSTOT - repeated exposureNot classified based on available dataAspiration hazardNot classified based on available data.Other adverse effectsCharacteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

12. ECOLOGICAL INFORMATION

Ecotoxicity

Not classified based on available data.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

| Chemical Name | Toxicity to algae | Toxicity to daphnia and | Toxicity to fish | Toxicity to |
|-------------------------------|-------------------------|-----------------------------|-----------------------------|----------------|
| | | other aquatic invertebrates | | microorganisms |
| Lubricating oils (petroleum), | EL50 (48h) > 100 mg | EL50 (48h) > 10000 mg/l | LL50 (96h) > 100 mg/l | |
| C20-50, hydrotreated neutral | (Pseudokirchnerella | (Daphnia magna - OECD | (Oncorhynchus mykiss - | |
| oil-based | subcapitata - OECD 201) | 202) | OECD 203) | |
| 72623-87-1 | | LL50 (24h) > 10000 mg/l | | |
| | | (Gammarus pulex - OECD | | |
| | | 202) | | |
| | | LL50 (48h) > 10000 mg/l | | |
| | | (Gammarus pulex - OECD | | |
| | | 202) | | |
| | | LL50 (72h) > 10000 mg/l | | |
| | | (Gammarus pulex - OECD | | |
| | | 202) | | |
| | | LL50 (96h) > 10000 mg/l | | |
| | | (Gammarus pulex - OECD | | |
| | | 202) | | |
| Alkoxylated long chain | EL50(72)h 0.0538 mg/l | EC50(48h) 0.043 mg/l | LC50(96h) 0.1 mg/l (Danio | |
| alkylamine | Pseudokirchneriella | (Daphnia magna - OECD | rerio - OECD Guideline 203) | |
| ^ | subcapitata) | Guideline 202) | | |



according to the Global Harmonized System

SDS # : 082513

ATF III

Issuing date: 2018-02-02

Revision Date: 2019-05-15

Version 1.01

| 2-(2-heptadec-8-enyl-2-imid | EC50 (72h) 0.03 mg/l | EC50(48h) 0.136 mg/l | LD50 (96h) 0.3 mg/l | |
|-----------------------------|--------------------------|----------------------------|---------------------------|--|
| azolin-1-yl)ethanol | (Desmodesmus subspicatus | (Daphnia magna semi-static | (Brachydanio rerio - OECD | |
| 95-38-5 | static - OECD 201) | - OECD 202) | 203) | |

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

| Chemical Name | Toxicity to algae | Toxicity to daphnia and other aquatic invertebrates | Toxicity to fish | Toxicity to microorganisms |
|--|------------------------|--|---|-------------------------------|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based 72623-87-1 | NOEL (72h) >= 100 mg/l | | NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox) NOEL (96h) > 100 mg/l (Pimephales promelas - OECD 203) | |

Effects on terrestrial organisms

No information available.

Persistence and degradability

No information available.

Bioaccumulative potential

Product Information No information available.

logPow No information available

Component Information

| Chemical Name | log Pow |
|--|---------|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based - 72623-87-1 | 4.1 |
| 2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol - 95-38-5 | 7.51 |

Mobility

.

| Soil | Given its physical and chemical characteristics, the product generally shows low soil mobility. |
|-------|---|
| Air | Loss by evaporation is limited. |
| Water | The product is insoluble and floats on water. |



according to the Global Harmonized System

| SDS # : 082513 | ATF III | |
|--|--|-------------------------------|
| Issuing date: 2018-02-02 | Revision Date: 2019-05-15 | Version 1.01 |
| Other adverse effects | | |
| General Information | No information available. | |
| 13. DISPOSAL CONSIDERA | TIONS | |
| Waste from Residues / Unused Products | Should not be released into the environment. Do not empty accordance with all applicable national environmental laws recycling is preferred to disposal or incineration. | |
| Contaminated packaging | Empty containers should be taken to an approved waste ha disposal. | andling site for recycling or |
| Other information | Refer to section 8 for safety and protective measures for dis | sposal personnel. |

| ADR/RID | Not regulated |
|----------|---------------|
| IMDG/IMO | Not regulated |
| | Not regulated |
| ADN | Not regulated |

15. REGULATORY INFORMATION

14. TRANSPORT INFORMATION

International Inventories

Australia (AICS) Japan (ENCS) Philippines (PICCS) Korea (KECL) Europe (EINECS/ELINCS/NLP) U.S.A. (TSCA) Canada (DSL/NDSL) China (IECSC)

Further information

No information available



according to the Global Harmonized System

SDS # : 082513

ATF III

Issuing date: 2018-02-02

Revision Date: 2019-05-15

Version 1.01

National regulatory information

No information available

16. OTHER INFORMATION Issuing date: 2018-02-02

Revision Date: Revision Note 2018-02-02 2019-05-15 No information available.

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

Legend

Section 8 ACGIH - American Conference of Governmental Industrial Hygienists

TWA - Time Weight Average

STEL - Short Term Exposure Limits

S* - Skin notation

Ceiling: Maximum limit value

Additional details on the supplier of the product

| U.A.E Supplier | TOTAL MARKETING MIDDLE EAST FZE Burjuman Business Tower, 11th Floor Sheikh Khalifa Bin Zayed Road Dubai P.O. Box 14871 U.A.E Tel: +971 4 709 50 00 Fax: +971 4 351 91 54 | CAMBODIA Supplier | TOTAL CAMBODGE ANINA Building 6th Floor, No 240, St. 271, B.P600, 12351 Phnom Penh, Cambodia Tel: +855 23 218 630 Fax: +855 23 217 662 |
|----------------|--|----------------------|--|
| INDIA Supplier | TOTAL OIL INDIA PVT. LTD. 3rd Floor, The Leela Galleria, Andheri - Kurla Road, Andheri (East), Mumbai Maharashtra State, | | |



according to the Global Harmonized System

SDS #: 082513

ATF III

Issuing date: 2018-02-02

Revision Date: 2019-05-15

Version 1.01

| | INDIA 400059 Tel: +91 22 6723 2500 Fax: +91 22 6723 2600 | JORDAN Supplier | TOTAL JORDAN Reem Center, 4th Floor 244 Arar Street, Wadi Saqra P.O. Box 831285, Amman 11183 Jordan Tel: +962 6 500 80 05 Fax: +962 6 500 80 08 |
|------------------------------|--|--------------------------|---|
| LEBANON Supplier | TOTAL LIBAN Rue Achrafieh, Imm. Tilal Bloc B, 2ème Etage B.P. 11-3636 Beyrouth - Liban Tel : + 961 1 21 22 50 Fax: + 961 1 21 21 33 | PAKISTAN Supplier | TOTAL PARCO PAKISTAN LTD 10 Tariq Block, New Garden Town Lahore 54700, Pakistan Tel: +92 42 111 709 709 Fax: +92 42 354 683 66 |
| PAPUA NEW GUINEA Supplier | TOTAL OIL ASIA PACIFIC PTE LTD - PNG Cuthbertson Street Level 4, Cuthbertson House PO BOX 1784 Port Moresby Papua New Guinea Tel: +675 320 2141 Fax: +675 320 3951 | SAUDI ARABIA Supplier | SAUDI TOTAL PETROLEUM PRODUCTS CO. LTD 704, Zahran Business Center Sultan street - Tower A , 7th floor PO Box 4861, Jeddah 21463 K.S.A Tel: +966 12 22 56 300 Fax: +966 12 22 56 311 |

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet