




# ELF MOTO<sup>2</sup> OFF ROAD

2-stroke motor oil

## KEY DATA


- MOTORCYCLE RANGE



- INTERNATIONAL STANDARDS

- ✓ API TC
- ✓ JASO FD
- ✓ ISO L-EGD

- LEVEL



- 2-STROKE MOTOR OIL
- SYNTHETIC BASED

## APPLICATIONS

**ELF MOTO<sup>2</sup> OFF ROAD** is a lubricant that is particularly recommended for all types of 2-stroke engine motorcycles, in compliance with API TC, JASO FD and ISO L-EGD international standards.

**ELF MOTO<sup>2</sup> OFF ROAD** is recommended for driving through urban traffic as well as rural conditions and for the most severe off road use. **ELF MOTO<sup>2</sup> OFF ROAD**'s composition is compatible with lead-free fuels. The product is pre-diluted to simplify separate lubrication and fuel mixtures. Adjust the oil content according to the manufacturer's recommendations.

**ELF MOTO<sup>2</sup> OFF ROAD** is fortified with synthetic base oils. It provides hydrodynamic lubrication and preserves your engine's power and original performance. The selected fluid viscosity and solvents facilitate miscibility between the lubricant and the fuel, even in applications with separated fuel / lubricant tanks.

## CUSTOMER BENEFITS

- Clean combustion:** the mixture's clean combustion guarantees the thermal breakdown of the additives and base oils. **ELF MOTO<sup>2</sup> OFF ROAD** prevents clogging thanks to the additives and balanced base oils it contains
- Protection, power, endurance:** The additives - which have been extremely carefully selected - prevent deterioration due to moving part wear. Guarantees long engine life and reduces maintenance costs (servicing and repair).

[www.elfmoto.com](http://www.elfmoto.com)



## CHARACTERISTICS\*

Test	Unit	Result
Density at 15°C	kg/m <sup>3</sup>	869
Sulphated ash content	% weight	0.07
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	76.1
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	10.9
Pour Point	°C	-21
OC Flash Point	°C	120
Colour	-	Blue

\*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

## RECOMMENDATIONS FOR USE

Before using the product, the vehicle's user guide should be checked. This lubricant has been designed to lubricate 2-stroke engines fitted with independent greasing systems or for use as part of a mixture in percentages recommended by the manufacturer.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

## HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at [www.quickfds.com](http://www.quickfds.com).

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.

TOTAL Lubrifiants  
Immeuble Le Spazio  
562, avenue du Parc de l'île  
92029 Nanterre Cedex  
France

Last update of this datasheet: 06/2020

# ELF MOTO<sup>2</sup> OFF ROAD



Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at [www.lubrifiants.total.fr](http://www.lubrifiants.total.fr).