

TOTAL FINADET MFA SF

Low Odour Water-Based Degreaser

KEY DATA

- FINADET MFA SF is a concentrated, quickbreak degreaser for use in industry.
- Water-based; contains no solvents.
- Low odour making it suitable for underground or enclosed environments
- Effectively removes grease and oil in high grime areas
- Fully biodegradable
- Will not affect plastics and rubber components
- Highly alkaline formulation

NOTE: Avoid contact of strong solutions with unprotected polished aluminium, magnesium and alloys.

Customer benefits

- ✓ **Odourless:** Suitable for use in industry and mines sites where underground usage is required.
- ✓ **Effective performance:** Highly suited to tackling grease in the presence of high grime loading.
- ✓ **Anti-corrosion:** Inhibits ferrous metal corrosion.
- ✓ **Water-based:** Contains no solvents. Non-flammable.
- ✓ **Plastics and rubber suitability:** Will not affect plastics and rubber.
- ✓ **Biodegradable:** Quickbreak formulation for easier disposal

Directions for use

- Spray on or brush. Apply liberally to surfaces to be cleaned. Allow to stand for 5 minutes then rinse.
- Concrete cleaning. Apply to concrete and allow 2-3 minutes to soak in. Scrub with yard broom and then rinse off with water.
- Heavy grease and grime loads: Dilute 1 part with 5 parts water.
- Normal under bonnet conditions: Dilute 1 part with 15 to 30 parts water.
- Hard surfaces cleaning (vinyl, paintwork, fiberglass): Dilute 1 part with 15 to 30 parts water.

Characteristics*

Test	Result
Appearance	Green Liquid
Density at 25°C	1.05 – 1.08
pH	12.8 neat
Water Solubility	Miscible in all proportions
Phosphates	Yes

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

Recommendations for use

Before using the product, the vehicle's maintenance guide should be checked.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

Health, safety and the environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at:

<https://sdstotalms.total.com/TotalPullWebsite/en>

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.

TOTAL OIL AUSTRALIA PTY LTD
Level 23, 600 Bourke St,
Melbourne, VIC, 3000
Australia

TOTAL FINADET MFA SF
Last update of this datasheet: 03/2021

www.totaloil.com.au

