

# RUBIA MINI PLUS

## 15W-40



---

Mineral lubricant for diesel engines

---

### SPECIFICATIONS AND APPROVALS

API CH-4

---

### APPLICATIONS

- ❖ TOTAL Rubia Mini Plus 15W-40 is recommended for turbocharged or naturally-aspirated diesel engines of commercial vehicles (trucks, buses, vans, pick-ups, taxis...), and for all off-road applications requiring API CH-4 performance.
  - ❖ This lubricant is well suited for all industrial vehicles operating under severe service conditions (high temperature, frequent stops...).
  - ❖ TOTAL Rubia Mini Plus 15W-40 is specifically recommended for diesel engines from heavy duty to extremely heavy duty.
- 

### PERFORMANCES AND CUSTOMER BENEFITS

- ❖ TOTAL Rubia Mini Plus 15W-40 has excellent oxidation resistance, guaranteeing efficient engine protection under normal and severe conditions.
  - ❖ Detergent, dispersant and anti-wear properties keep the engine clean and enable effective control of soot, sludge and piston deposits.
  - ❖ TOTAL Rubia Mini Plus 15W-40 exhibits superior protection against heat and wear ensuring long engine life.
- 

### PHYSICAL AND CHEMICAL CHARACTERISTICS

Parameter	Unit	Method	Typical Value
Density	kg/m <sup>3</sup>	ASTM D 1298	880
Kniematic Viscosity at 40°C	cSt	ASTM D 445	108
Kinematic Viscosity at 100°C	cSt	ASTM D 445	14
Viscosity Index		ASTM D 2270	130

---

#### Total Lubricants India Ltd.

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059.

Tel. : 022 66407700 Fax : 022 66407720

# RUBIA MINI PLUS

## 15W-40



---

### RECOMMENDATIONS

- ❖ Before using the product, it is important to check the service manual of the vehicle: the drain is carried out according to the manufacturer's requirements.
  - ❖ The product should not be stored at a temperature above 60 °C. Exposure to strong sunlight, extreme cold or high temperature variations must be avoided.
  - ❖ All packages should be protected from bad weather conditions. The drums should be stored horizontally to avoid a possible contamination by water and the damage of the product label.
- 

**Total Lubricants India Ltd.**

Head Office : 3rd Floor, The Leela Galleria, Andheri-Kurla Road, Andheri (E), Mumbai - 400 059.  
Tel. : 022 66407700 Fax : 022 66407720